

**AMENDMENTS TO THE CLAIMS**

**What is claimed is:**

1. (currently amended) A floor care cleaning apparatus, comprising:
  - a nozzle assembly having an intake opening;
  - a canister assembly pivotally connected to said nozzle assembly;
  - a suction generator carried on one of said nozzle assembly and said canister assembly;
  - a dirt collection vessel carried on one of said nozzle assembly and said canister assembly; and
  - a control handle assembly pivotally connected to said canister assembly, said control handle assembly having an operating handle adjacent a first end and a carrying handle adjacent a second end, said control handle assembly being selectively displaceable between an operating position and a storage position.
2. (original) The floor care cleaning apparatus of claim 1 further including a hub on one of said canister assembly and said control handle assembly and a boss engaging said hub on the other of said canister assembly and said control handle assembly.

3. (original) The floor care cleaning apparatus of claim 2 further including a first projection on one of said canister assembly and said control handle assembly and a first projection receiver on the other of said canister assembly and said control handle assembly.

4. (original) The floor care cleaning apparatus of claim 3, wherein said first projection receiver includes a first stop engaging said first projection when said control handle assembly is in said operating position and a second stop engaging said first projection when said control  
5 handle assembly is in said storage position.

5. (original) The floor care cleaning apparatus of claim 4, wherein said first projection receiver is a channel extending in a limited arc radially around an axis about which said control handle assembly pivots with respect to said canister assembly.

6. (original) The floor care cleaning apparatus of claim 5, further including a locking mechanism for locking said control handle assembly in said operating position or said storage position.

7. (original) The floor care cleaning apparatus of claim 6, wherein said locking mechanism includes a guide track carried on one of said canister assembly and said control handle assembly and a displaceable latch received in said guide track.

8. (original) The floor care cleaning apparatus of claim 7,  
further including a first latch receiver receiving said latch when said  
control handle assembly is in said operating position and a second latch  
receiver receiving said latch when said control handle assembly is in said  
5 storage position, said first and second latch receivers being carried on the  
other of said canister assembly and said control handle assembly.

9. (original) The floor care cleaning apparatus of claim 8,  
further including a means for biasing said latch into one of said first and  
second latch receivers.

10. (original) The floor care cleaning apparatus of claim 9,  
further including a slot carried by said hub and a retaining clip received in  
said slot to retain said control handle assembly and said canister assembly  
together.

11. (original) The floor care cleaning apparatus of claim 9,  
further including a second projection on one of said canister assembly and  
said control handle assembly and a second projection receiver on the other  
of said canister assembly and said control handle assembly.

12. (original) The floor care cleaning apparatus of claim 11,  
wherein said second projection receiver includes a first rib engaging said  
second projection when said control handle assembly is in said operating

position and a second rib engaging said second projection when said control handle assembly is in said storage position.

13. (original) The floor care cleaning apparatus of claim 12, further including an aperture in said hub substantially on said axis.

14. (original) The floor care cleaning apparatus of claim 13, further including an electrical power cord extending through said aperture.

15. (original) The floor care cleaning apparatus of claim 12, wherein said first projection is carried on said control handle assembly.

16. (original) The floor care cleaning apparatus of claim 15, wherein said second projection is carried on said control handle assembly.

17. (original) The floor care cleaning apparatus of claim 1, wherein said operating handle is a hand grip.

18. (original) The floor care cleaning apparatus of claim 1, wherein said carrying handle comprises a portion of a loop.

19. (currently amended) ~~The floor care cleaning apparatus of claim 1;~~ A floor care cleaning apparatus, comprising:  
a nozzle assembly having an intake opening;

a canister assembly connected to said nozzle assembly;  
a suction generator carried on one of said nozzle assembly  
and said canister assembly;

5 a dirt collection vessel carried on one of said nozzle  
assembly and said canister assembly; and

a control handle assembly pivotally connected to said  
canister assembly, said control handle assembly having an operating  
handle adjacent a first end and a carrying handle adjacent a second end,  
said control handle assembly being selectively displaceable between an  
10 operating position and a storage position wherein said control handle  
pivots relative to said canister assembly about an axis A, said axis A being  
a distance  $D_1$  from a bottom of said floor cleaning apparatus and said  
operating handle includes a stabilizer, said stabilizer being a distance  $D_2$   
from said axis A wherein  $D_2$  is less than  $D_1$  by about 0.5 to about 2.0 cm.

20. (original) The floor cleaning apparatus of claim 19, wherein  
at least one wheel is carried on an axle on said canister assembly and said  
stabilizer is spaced rearwardly from said axle by a distance of about four  
inches when said control handle is in said storage position.

21. (currently amended) A floor cleaning apparatus,  
comprising:

a housing;

a suction generator and a dirt collection vessel carried on  
said housing;

a control handle assembly pivotally connected to said  
housing, said control handle assembly including a hand grip ~~for~~  
5 ~~manipulating said floor cleaning apparatus during cleaning~~ and a stabilizer  
for engaging ~~said floor~~ a floor when storing said floor cleaning apparatus.

22. (currently amended) A method for preventing the  
inadvertent tipping of a floor cleaning apparatus, comprising:

providing a control handle assembly for ~~said floor~~ a floor  
cleaning apparatus that is displaceable between operating and storage  
5 positions; and

configuring said control handle assembly so that a portion  
thereof is adjacent the floor when said control handle assembly is in said  
storage position whereby engagement of said portion with the floor  
prevents tipping over of said floor care cleaning apparatus.